

008 1
012
013
002
003
004
003
005
006
003
004

O₂

ORBISPHERE 410

O₃



Precise process monitoring



EXCELLENCE IN PROCESS ANALYTICS

O₂

O₃

ORBISPHERE 410

The ORBISPHERE 410 offers precise, process monitoring capability.

Designed to complement the ORBISPHERE high quality oxygen and ozone sensors these instruments provide accurate, repeatable trace level measurements and an impressive level of data management.

These process monitoring instruments are designed for applications in the power generation, electronics, life sciences, beverage, chemical and water treatment industries.



Operation

All functions of ORBISPHERE 410 instruments are accessed through the monochrome, touch screen. This screen acts as display and keyboard.

ORBISPHERE 410 instruments are designed for ease of use. After simple installation the system is measuring your process in minutes.

The main measurement window continuously displays real time process readings, graphed sensor trends (user selectable from last 1 minute to last 1 hour), alarm limits, temperature and event occurrence.

Sensor life can be extended during CIP cleaning and other high temperature procedures through automatic isolation of the sensor above a pre-selectable level. Common interference effects due to CO₂, H₂S, salinity and chlorinity can be eliminated during the configuration process.

Measurement, configuration, calibration and standard service routines are called up using the simple to follow menus on screen. Access levels are password protected supporting regulatory compliance to standards such as ISO and 21 CFR Part 11, ensuring problem free audits and reducing compliance costs.

Benefits

- High level of measurement accuracy and rapid response time means reliable and effective process monitoring
- Easy to use, intuitive software navigation is simple to use for line operators, flexible enough to meet the needs of technical personnel
- The monochrome, touch-screen in a stainless steel enclosure conforming to IP65 defines a robust unit built to handle the industrial environment
- Data storage of up to 1000 measurements, last 1000 operator actions and details of last 10 calibrations

- *Dissolved concentrations from 0.1 ppb to super-saturation*
- *Easy to use, intuitive software using clear, monochrome touch-screen*
- *Internal diagnostics and reminders for maintenance and calibration*
- *IP65 stainless steel enclosure designed for harsh industrial environments*
- *Multiple communication options including USB, Ethernet and Profibus*

Calibration

The ORBISPHERE 410 software defines the step-by-step process for calibration of both measured gas and interferences. ORBISPHERE's unique air cal or direct value calibration may be used.

Traceability is ensured through a report that is generated following each calibration. A log file, containing details of the previous 10 calibrations undertaken, further supports traceability.

Barometric pressure calibration for the instrument's internal sensor may be simply carried out by comparison with a precision certified barometer.

Communication

Digital communication uses industry standard protocols including Profibus DP, USB, and Ethernet in addition to traditional analog outputs and alarm relays. These may all be configured in terms of function, content and behavior.

ORBISPHERE 410 instruments are compatible with ORBISPHERE O₂ and O₃ electrochemical sensors including Smart sensors. Smart sensors can be calibrated in the laboratory before installing on-line and store their own calibration information, so allowing laboratory precision calibration and minimizing process downtime.

Validation and Diagnostics

To ensure continuous high performance and simplify maintenance ORBISPHERE 410 instruments offer a number of diagnostic features including:

- Notification that calibration is due - ensures QC procedural compliance
- Notification that a sensor service is due – optimal preventative maintenance planning
- Sensor service diagnostics - minimizes downtime
- System alarms transmitted through analog output – continuous status indication



- Internal diagnostics simplify trouble-shooting and issue reminders for maintenance and calibration
- Software password protection offers five levels of controlled access, minimizing the risk of errors in operation or configuration
- Adjustable alarms and outputs provide assurance that any out of specification events are appropriately registered
- Suitable for sampling dissolved concentrations from ppb to supersaturation, and gaseous concentrations from ppm to percent level

ORBISPHERE 410 instruments are available in two versions.

Wall and pipe version Mounting is facilitated by use of simple to attach brackets that allow adjustment of the instrument to afford optimum screen viewing angle.

Panel mount version Quick and easy mounting from the front of the panel using concealed screws.

Performance specifications*

Measurement		Resolution: 0.1 ppb oxygen Accuracy and response time: determined by sensor
Sensor options		ORBISPHERE 311XX electrochemical oxygen sensors ORBISPHERE 313XX electrochemical ozone sensors ORBISPHERE 31XXs oxygen or ozone Smart sensors
Units	<ul style="list-style-type: none"> ■ Gas concentration ■ Temperature ■ Pressure 	Configurable for gas or liquid phase with multiple unit options Sample temperature with unit options (K, °C, °F) Barometric pressure with multiple unit options
Sample frequency		Continuous measurement
Interference correction		Chlorinity correction Salinity correction CO ₂ insensitivity H ₂ S insensitivity
Communications		RS485, USB client, USB Host, Ethernet, Profibus DP (optional)
Analog output		Three smart 4-20mA or 0-20mA (software configurable), R maximum 600Ω
Relays		Three measurement alarm relays (2A-30 VDC or 0.5A-50 VAC) One instrument system alarm relay (2A-30 VAC or 0.5A-50 VDC)
CE Certifications		CE Electromagnetic compatibility standards: EN 61326-1- A1 & A2 CE Safety standard: EN 61010-1 ETL, conforming to UL 61010-1 and CSA 22.2 No. 61010-1
Calibration data		Holds calibration records for last 10 calibrations
Data storage		Rolling or store once mode for up to 1000 measurements and 1000 last operator actions
Password protection		Five levels of authorised access to configuration and data management
Power requirements	<ul style="list-style-type: none"> ■ Mains units 	Universal 85-264 VAC @50/60 Hz, 25 VA; or 10-36 VDC, 25 W
Power consumption		Maximum 6 W
Operating limits		-5° C to 50° C 0 to 95 % non-condensing relative humidity
Thermal cut-off		Configurable thermal cut-off for sensor protection
Enclosure	<ul style="list-style-type: none"> ■ Wall/pipe ■ Panel 	Stainless steel, IP65 Aluminium, IP65
Display		Monochrome STN 320 x 240 pixels with LED backlight
Keypad		Touch-screen panel
Languages		5 major European languages are available as standard Chinese (C), Japanese (J) or Korean (K) versions can be ordered specifically
Dimensions	<ul style="list-style-type: none"> ■ Wall/Pipe ■ Panel 	Height: 230.5 mm / Depth: 160 mm / Width: 250 mm Height: fascia - 156 mm, enclosure - 123 mm / Depth: 250 mm Width: fascia - 220 mm, enclosure - 214 mm
Weight	<ul style="list-style-type: none"> ■ Wall/Pipe ■ Panel 	3.4 kg 2.9 kg

* Certain elements of the performance specification are only available as options to the standard unit.
Please discuss your specific needs with a HACH ULTRA representative.

Global Headquarters

6, route de Compois - CP 212
1222 Vézenaz - Geneva - Switzerland
Tel ++ 41 (0)22 594 64 00
Fax ++ 41 (0)22 594 64 99

Americas Headquarters

481 California Avenue
Grants Pass - Oregon 97526 - USA
Tel 1 800 866 7889 / 1 541 472 6500
Fax 1 541 472 6170

© 2008 HACH ULTRA ANALYTICS. Trademarks are property of their respective owners. Specifications are subject to change without notice.

ANATEL HIAC ORBISPHERE HYT MET ONE POLYMETRON

hachultra.com

